

MAXTER GLOVE MANUFACTURING SDN BHD GLOVE SPECIFICATION

1. Product : 3.2 Mil (3.6g) Black Powder Free Nitrile Examination Gloves
2. Material : Nitrile
3. Type : Non Sterile
4. Glove Design & Feature : Ambidextrous and finger textured.
5. Cuff : Beaded
6. Usage : For Single Use Only
7. Colour : Black
8. Packaging : 200 ± 4 pcs/inner, 10 inners/carton or
100 ± 2 pcs/inner, 10 inners/carton

Size	Glove Weight (g)	Palm Width (mm)		Length (mm)	
		ASTM D6319	MAXTER	ASTM D6319	MAXTER
XS	3.0 ± 0.2	70 ± 10	70 – 79	Min. 220	Min. 240
S	3.3 ± 0.2	80 ± 10	80 – 89	Min. 220	Min. 240
M	3.5 ± 0.2	95 ± 10	90 – 99	Min. 230	Min. 240
L	3.8 ± 0.2	110 ± 10	100 – 109	Min. 230	Min. 240
XL	4.1 ± 0.2	120 ± 10	110 – 119	Min. 230	Min. 240

Location of Thickness Measurement	Single Wall (mm)	
	ASTM D6319	MAXTER
Finger	Min 0.05	Min 0.10
Palm	Min 0.05	Min 0.06
Cuff	N/A	Min 0.05

	Before Aging		After Aging	
	ASTM D6319	MAXTER	ASTM D6319	MAXTER
Tensile Strength (MPa)	Min. 14	Min. 14	Min. 14	Min. 14
Elongation (%)	Min. 500	Min. 500	Min. 400	Min. 400
Force at Break (N)	N/A	Min. 6	N/A	Min. 6

12. Protein Content : Not applicable.
13. Powder Level : Max. 2 mg/ glove.
14. Compliance Standards : ASTM D6319, EN 455 Part 1, 2, 3 & 4.

Inspection Criteria (Sampling & Inspection ISO 2859)		Inspection Level		AQL
		G1	G1	1.5
	Watertight Test	G1	G1	2.5
	Major Defects	G1	G1	4.0
	Minor Defects	G1	G1	4.0
	Dimensions	S2	S2	4.0
	Physical Properties	S2	S2	4.0

16. Quality Assurance : ISO 9001 certified by SGS (UK) and SIRIM (Malaysia)
ISO 13485 certified by SGS (UK)

Prepared by :

Yap Peak Geoh
QA & RA Manager

